

USB WiFi Camera Calibration Dongle

SKU: USBCAL



Key Features

- **Plugs in-line** with the Proxicam Smart Camera
- **Creates an ad-hoc wireless network** for the Proxicam Smart Camera
- **Provides a temporary peer-to-peer connection** for system setup and camera configuration

Technical Specifications

Input Voltage	5V VDC
Current Draw	<1A
Operating Frequency (WiFi)	2412MHz-2472MHz, 5180MHz-5240MHz, 5745MHz-5825MHz
Channels (WiFi)	13 Channels for 2412MHz- 2472MHz 7 Channels for 5180MHz-5240MHz 8 Chan- nels for 5745MHz-5825MHz
Channels (WiFi)	802.11a:5.51dBm; 802.11n-HT20:5.51dBm; 802.11n-HT40:5.06dBm; 802.11ac-VHT20:5.41dBm; 802.11ac-VHT40:5.72dBm; 802.11ac-VHT80:5.22dBm
Data Rate	802.11a: 6/9/12/18/24/36/ 48/54Mbps 802.11n: up to 300Mbps 802.11ac: up to 866.6Mb-
Modulation(WIFI)	CCK,OFDM,BPSK,GPSK,16-QA- M,64-QAM for 2.4G WIFI OFDM/BPSK/QPSK/CCK/ DQPSK/DBPSK for 5G WIFI
TPC Function	No
Antenna Type(WIFI)	Integral antenna
Antenna Gain(WIFI)	2dBi
Interface	USB 2.0
IEEE Standard	802.11ac
Operating Temperature	-20° ~ +60°C

IMPORTANT

The Proxicam USBCAL is not water or dust proof and must be removed after use.

Do Not Leave Installed In The Machine.