

This technical data sheet refers to the following Lighthouse product(s):

CPMS98, 75 Micron Polycarbonate Overlamine

DESCRIPTION

This is a clear velvet embossed polycarbonate film coated with a clear permanent adhesive. UL recognised for indoor use with occasional exposure to lubricating oil and water.

APPLICATION

Face plates, nameplates and decorative trim parts.

PHYSICAL PROPERTIES	DESCRIPTION
Film Thickness	75 micron
Adhesive	Permanent Acrylic
Initial Tack	High
Ultimate Adhesion	High
Minimum Application Temperature	10°C
Service Temperature	-40°C to 100°C
Outdoor Durability	Not recommended for outdoor use
UL number	UL approved MH10170 (N)
Shelf Life	2 years

IMPORTANT NOTICE

All Lighthouse products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects.

Published information concerning Lighthouse products is based on research, which the Company believes to be reliable, although such information does not constitute a warranty.

Because of the variety of uses of Lighthouse products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use. We recommend the purchaser conducts their own testing to determine the suitability for their required application. The purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice