

This technical data refers to the following Lighthouse products:

**Yellow Polyester**

**Description**

Gloss finish metallised polyester film coated with a permanent acrylic adhesive.

**Applications**

This metallised polyester film provides excellent opacity when overlaying dark substrates. The permanent acrylic adhesive provides high level of adhesion to an array of smooth and slightly textured substrates.

This product offers good chemical and temperature resistance ideal for marking equipment and components including barcode and asset labels, rating plates etc.

**Technical Information**

Thickness	Film Liner	62 microns 130 gsm
Service Temperature		-40°C to 134°C
Minimum Application Temperature		10°C
Adhesion	Initial tack Ultimate adhesion	Low High

Compliance	RoHS 2 REACH UL File No. MH18338 – FR1015-50
Shelf Life (When stored at 15-20°C & 50-60% relative humidity)	2 years

Compatible Ribbons for Printing	Speciality Ribbon Range
---------------------------------	-------------------------

**IMPORTANT NOTICE**

All Lighthouse products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects.

Published information concerning Lighthouse products is based on research, which the Company believes to be reliable, although such information does not constitute a warranty.

Because of the variety of uses of Lighthouse products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use. We recommend the purchaser conducts their own testing to determine the suitability for their required application. The purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages.

All specifications are subject to change without prior notice.