




### TECHNICAL DATA (Continued)

Resistance To Solvents And Chemicals	Reagent	Recommendation
Product laminated to stainless steel panel and allowed to condition for 24 hrs at room temperature before testing. Sample was covered with reagent to the point that edges of product are also exposed to the reagent. The product is exposed to reagent for 1 hour at room temperature then reagent is removed and product is immediately tested for scrape resistances, delaminating and other visual effect.	Water	Recommended
	10% salt water	Recommended
	Bleach	Recommended
	Trichloroethylene	Not Recommended
	25% Sulphuric Acid	Recommended
	1% Sodium Hydroxide	Intermittent Contact Only
	Unleaded Gasoline	Intermittent Contact Only
	Diesel Fuel	Intermittent Contact Only
	Hydraulic Fluid	Recommended
	50% anti-freeze in water	Recommended
	MEK	Not Recommended
Mineral spirits	Recommended	
99% IPA	Recommended	

### Material Compliance

<b>Luminous Compliance</b>	DIN 67510, ASTM 2072, ISO 15370, IMO RES A. 752 (18), PSPA Class B
<b>RoHS</b>	RoHS Directive 2002/95/EC (Restrictions of the Use of Certain Hazardous Substances in Electronic Equipment)
<b>REACH</b>	Registration Evaluation and authorisation of Chemicals (EU Directive 1907/2006/EC)
<b>Lloyd's Register Maritime &amp; Coastguard Agency IMO Resolution A.752(18)</b>	<p>Complaint with the essential Fire protection requirements of Maritime Equipment Directive (MED) 96/98/EC as modified by commission Directives 98/85/EC, 2001/53/EC, 2002/75/EC, 2002/84/EC, 2008/67/EC, 2009/26/EC, 2010/68/EU, 2011/75/EU, 2013/52/EU &amp; 2014/93/EU</p> <div style="text-align: center;">  <p>0038/15</p> </div>
<b>Compatible Ribbons for Printing Speciality Resin Ribbons.</b>	CPMSR240, CPMSR241, CPMSR242, CPMSR243 CPMSR244

### IMPORTANT NOTICE

All Lighthouse products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects.

Published information concerning Lighthouse products is based on research, which the Company believes to be reliable, although such information does not constitute a warranty.

Because of the variety of uses of Lighthouse products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use. We recommend the purchaser conducts their own testing to determine the suitability for their required application. The purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages.

All specifications are subject to change without prior notice.